



CHARACTERISTICS

- Primer used for promoting adhesion
- Undercoat for silicone sealants

APPLICATIONS

- On non porous materials, certain plastics, paints and ceramics
- For porous materials, **Primer DL 783** is recommended.

TECHNICAL CHARACTERISTICS	
Base	Mixture of silicone and resins with reactivating addition
Colour	Colourless, transparent
Density	0.86 g/cm ³
Viscosity	Liquid
Drying time	30 min.
Flash point	< 21°C
Consumption	< 10,75 m ² /l
Processing temperature	Room temperature
Shelf life, in the original closed packing below +25°C	Min. 9 months

PACKING
Aluminium bottle of 250 ml - 117 bottles/pallet
Aluminium bottle of 1 l - 200 bottles/pallet

METHOD OF USE

Application

- The primer should be applied on the surface with a paintbrush.
- The sealant has to be applied within 16 hours.
- For very porous substrates a second layer of primer is necessary

Cleaning

Tools: nitro-thinner, M.E.C.

SAFETY

Safety data sheet available on request.

This technical data sheet replaces all previous editions. The data on this sheet have been compiled according to the last laboratory report. Technical characteristics can be changed or adapted. We are not responsible for any incomplete information. Before use, one needs to ensure that the product is suitable for his application. Therefore, tests are necessary. Our general conditions apply.